



## **PRODUCT FEATURES**

- + Amplify and extend RS-232 signals beyond 15.24m (50 ft) limit
- + Daisy-chain multiple repeaters for even extra range
- + Boost lower power RS-232 ports
- + Data rates up to 115.2 kbps
- + Quick, convenient in-line installation
- + Power supply required (not included, sold separately)

## **OVERVIEW**

Model BB-232LB9R is a 9-pin RS-232 repeater that re-transmits all 8 signals and carries the ground line through. Many computers, laptops and desktops feature low-power versions of RS-232 ports that are unable to drive portpowered devices or full-length RS-232 cabling.

Model BB-232LB9R amplifies these weak signals up to the RS-232 Standard for uses such as running port-powered devices (see Figure 1). It is suitable for extending full-powered RS-232 cable runs beyond the typical 15 to 30 meters (50-100 t) distance.(see Figure 2).

An external power supply is required, not included, sold separately. Model BB-SMi6-12V-P230C1 is recommended.




Figure 1. Boosting Low-power Ports




Figure 2. Extending Cable Runs

## **ORDERING INFORMATION**

MODEL NO.	DESCRIPTION
BB-232LB9R	9-pin RS-232 Line Repeater, DB9F to DB9M

**ACCESSORIES - sold separately** 

BB-SMi6-12V-P230C1 - power supply, 12 VDC, 6 Watt, 2.5mm plug, international

BB-9PAMF6 - DB9 male to female cable, 1.83 m (6 ft)

## **SPECIFICATIONS**

SERIAL TECHNOLOGY		
DCE Connector	DB9 female	
DTE Connector	DB9 male	
Data Rate	Up to 115.2 kbps	
POWER		
Supply Voltage	+12 to +16 VDC @ 40mA, maximum	
MECHANICAL		
Dimensions	7.9 x 4.3 x 2.1 cm (3.1 x 1.7 x 0.8 in)	
ENVIRONMENT		
Temperature Range	0 to +70 °C (+32 to +158 °F)	
REGULATORY / APPROVALS		
FCC Class B, CE		
CE - Directives	2014/30/EU – Electromagnetic Compatibility (EMC) 2011/65/EU – Reduction of Hazardous Substances (RoHS) 2012/19/EU – Waste Electrical and Electronic Equipment (WEEE)	
CE - Standards	EN 55032 Class B – Electromagnetic Compatibility of Multimedia Equipment – Emission requirements EN 55024 – Information Technology Equipment – Immunity Characteristics – Limits and methods of measurement	

All product specifications are subject to change without notice. BB-232LB9R\_1619ds

