

JetCard 1208 / 1208w

8-port RS-232 Universal PCI Card

- Supports 32-bit Universal PCI bus
- Easy-to-install driver and self-diagnostic utility
- High speed up to 921.6 Kbps
- Built-in 15KV ESD protection
- Supports 128-byte FIFO
- Supports on-board automatic hardware/ software flow control
- Wide Temperature -40°C ~ 80°C (JetCard 1208w)

Optional Accessories

CM62M9x8-100 8-port male DB-62 to male DB-9 connection cable, 100cm

CM62M25x8-100 8-port male DB-62 to male DB-25 connection cable, 100cm




CM62M9x8-100



CM62M25x8-100

Wide
Temp.



CE FC RoHS

JetCard 1204 / 1204w

4-port RS-232 Universal PCI Card

- Supports 32-bit Universal PCI bus
- Easy-to-install driver and self-diagnostic utility
- High speed up to 921.6 Kbps
- Built-in 15KV ESD protection
- Supports 128-byte FIFO
- Supports on-board automatic hardware / software flow control
- Wide Temperature -40°C ~ 80°C (JetCard 1204w)

Optional Accessories

CM37M9x4-60 4-port male DB-37 to male DB-9 connection cable, 60cm

CM37M25x4-60 4-port male DB-37 to male DB-25 connection cable, 60cm




CM37M9x4-60



CM37M25x4-60

Wide
Temp.



CE FC RoHS

JET/CARD



JetCard 1404 / 1404i

4-port RS-422 / 485 Universal PCI Card

- Supports 32-bit Universal PCI bus
- Easy-to-install driver and self-diagnostic utility
- High speed up to 921.6 Kbps
- Built-in 15KV ESD protection
- Automatic Flow Direction Switching Technology
- Supports 128-byte FIFO
- Supports on-board automatic hardware/software flow control
- Supports over current/ voltage protection
- Provides 2KV optical isolation (JetCard 1404i only)



CE FC  RoHS

Optional Accessories

CM37M9x4-60 4-port male DB-37 to male DB-9 connection cable, 60cm

CM37M25x4-60 4-port male DB-37 to male DB-25 connection cable, 60cm



CM37M9x4-60



CM37M25x4-60

JetCard 1402 / 1402i

2-port RS-422 / 485 Universal PCI Card

- Supports 32-bit Universal PCI bus
- Easy-to-install driver and self-diagnostic utility
- High speed up to 921.6 Kbps
- Built-in 15KV ESD protection
- Automatic Flow Direction Switching Technology
- Supports 128-byte FIFO
- Supports on-board automatic hardware/software flow control
- Supports over current/ voltage protection
- Provides 2KV optical isolation (JetCard 1402i only)



CE FC  RoHS