

# FOSTCDRI-PH-xx

## Heavy Industrial RS-232/422/485 to Fiber Optic Converter

- ✓ IEEE-61850-3
- ✓ IEEE 1613
- ✓ Multi-mode, Single Mode, ST, SC Versions
- ✓ -40 to 85°C Operating Temperature
- ✓ Rugged IP30 Metal Panel Mount Case
- ✓ 50G Shock, 4G Vibration
- ✓ 2kV Triple Isolation



The ILinx™ FOSTCDRI-PH-xx is our premium Heavy Industrial Serial to Fiber Optic Converter. Designed for rugged industrial environments, it has been put through some of the most exacting compliance tests in the industry. Meeting the requirements of IEC 61850-3 and IEEE 1613, it is suitable for installation in electrical substations. These specifications are more stringent than the NEMA TS1/TS2 requirements for transportation applications. Powerful isolation protects your equipment and data from damaging ground loops and surges. Additional isolation on the power supply circuits adds a third degree of protection.

Packaged in a rugged IP30 metal case, it converts serial signals to multi-mode or single mode fiber optic. Our bit-wise enabled circuitry automatically detects the data rate without setting a DIP switch.

In addition to direct point-to-point connectivity, it is capable of operating in multi-drop mode. This enables serial devices to communicate with up to 31 others in a fiber ring. Supporting mixed standards, you can replace other converters and add the EMI / RFI protection inherent to fiber optic communications.

Remember, when it comes to reliable communications in harsh industrial environments, B&B Electronics' ILinx™ brand converters and isolators are your number one choice.

### Specifications

#### Serial Technology

RS-232	TD, RD, GND
RS-422	TDA(-), TDB(+), RDA(-), RDB(+)
RS-485 4-Wire	TDA(-), TDB(+), RDA(-), RDB(+)
RS-485 2-Wire	Data A(-), Data B(+)
Serial Connector	5 Position, Removable Terminal Block
Data Rate	9.6 to 115.2 Kbps
Isolation	2 KV RMS, 1 minute
Surge Protection	600 W Peak Power Dissipation Clamping time < 1 pico-second
Industrial Bus Bias Termination	MODBUS ASCII / RTU Built-in, switchable 1.2KΩ XMT/RCV Built-in, switchable 120Ω

#### Fiber Optic Technology

Type / Wavelength	Multi-mode or Single Mode 1310 nM
Output Power (MM)	-19 (min), -14 (max) dBm
Output Power (SM)	-15 (min), -8 (max) dBm
RCV Sensitivity	≤ -32 dBm
Cable	62.5 / 125 μM (MM), 9 / 125μM (SM)
Data Rate	9.6 to 115.2 kbps
Distance	2 km (MM), 15 km (SM)
Fiber Light	Modulated

#### Power

Source	External
Power Connector	2 Position Removable Terminal Block
Input Voltage	10 to 48 VDC (56 VDC Maximum)
Power Consumption	0.9 W typical (2.6W with termination)

#### Terminal Blocks

Wire Size Accepted	28 to 12 AWG, Copper wire only
Pitch	5.08 mm
Insulation Resistance	≥500 MΩ @ 500 VDC
Maximum Torque	5 Kg / cm

#### Indicators

Power	Red LED
TD / RD (Each Port)	Green LED

#### Mechanical

Dimensions	5.2 x 3.7 x 1.3 in 132.4 x 92.9 x 33.0 mm
Enclosure	IP30 Metal, Panel Mount
Weight	0.46 lbs (208.65 grams)
MTBF	127103 Hours
MTBF Calc. Method	Parts Count Reliability Prediction

#### Environmental

Operating Temperature	-40 to 85°C (-40 to 176°F)
Storage Temperature	-40 to 85°C (-40 to 176°F)
Operating Humidity	0 to 95% Non-condensing

#### Regulatory

Approvals	FCC, CE, IEC 61850-3, IEEE 1613 UL C1 D2, File: E245458
-----------	--

### Ordering Information

FOSTCDRI-PH-MC	Serial to Multi-mode SC
FOSTCDRI-PH-MT	Serial to Multi-mode ST
FOSTCDRI-PH-SC	Serial to Single Mode SC
FOSTCDRI-PH-ST	Serial to Single Mode ST

**IEC 61850-3 Electro Magnetic Interference Specifications**

Test	Description	Test Level	Level
61000-4-2	ESD	Enclosure Contact	8 kV
		Enclosure Air	15 kV
61000-4-3	Radiated RFI	Enclosure Ports	10 V/m
61000-4-4	Burst (Fast Transient)	Signal Ports	4 kV @ 2.5 KHz
		DC Power Ports	4 kV
61000-4-5	Surge	Signal Ports	2 kV line to earth, 1 kV line to line
		DC Power Ports	2 kV line to earth, 1 kV line to line
61000-4-6	Induced (Conductive) RFI	Signal Ports	10 V RMS
		DC Power Ports	10 V RMS
61000-4-12	Damped Oscillatory	Signal Ports	2.5 kV common, 1 kV diff mode @ 1MHz
		DC Power Ports	2.5 kV common, 1 kV diff mode @ 1MHz
61000-4-16	Mains Frequency Voltage	Signal Ports	30 V Continuous, 300 V for 1 s
		DC Power Ports	30 V Continuous, 300 V for 1 s
61000-4-17	Ripple on DC Power Supply	DC Power Ports	10%

**IEEE 1613 C37.90 Electromagnetic Interference Specifications**

Test	Description	Test Level	Level
C37.90.3	ESD	Enclosure Contact	8 kV
		Enclosure Air	15 kV
C37.90.2	Radiated RFI	Enclosure Ports	10 v/m
C37.90.1	Fast Transient	Signal Ports	4 kV @ 2.5 kHz
		DC Power Ports	4 kV

**Environmental Specifications**

Test	Description	Test Level	Level
60068-2-1	Cold Temperature	Test Ad	(-)40 C, 16 Hours
60068-2-2	Dry Heat	Test Bd	(+)85 C, 16 Hours
60068-2-30	Humidity (damp heat cycle)	Test Dd	90% (non-condensing) (+)55C, 6 Cycles
IEC 60068-2-6	Vibration	Test Fc	4g
IEC 60068-2-27	Shock	Test Ea	50g
IEC 60068-2-32	Drop	---	6 faces, 3 edges, 1 corner, total 10 drops at 1 m

